

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number  
**WO 2005/045151 A2**

- (31) International Patent Classification<sup>7</sup>: **E04C**
- (21) International Application Number:  
PCT/US2004/035710
- (22) International Filing Date: 27 October 2004 (27.10.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/515,855 30 October 2003 (30.10.2003) US
- (71) Applicant (for all designated States except US): **ERICO INTERNATIONAL CORPORATION** [US/US]; 30575 Bainbridge Road, Suite 300, Solon, OH 44139 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **KERKAY, Colleen, M.** [US/US]; 26998 Valeside Lane, Olmsted Township, OH 44138 (US).
- (74) Agent: **PLATT, Jonathan, A.; RENNER, OTTO, BOISSELLE & SKLAR, LLP**, 1621 Euclid Avenue, Nineteenth Floor, Cleveland, OH 44115 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: REINFORCING BAR COUPLING



(57) Abstract: A reinforcing bar coupling includes a sleeve segment having a deformable interior section weaker than the balance of the segment. The deformable interior section, for example including deformable ribs, is configured to be pressed onto ends of reinforcing bars to be spliced together. The ribs deform onto and around deformations on exterior surfaces on the ends of the reinforcing bars. Thus locked to the ends of the reinforcing bars under pressure, the sleeve segment secures the ends of the reinforcing bars together. The sleeve segment may take any of a variety of forms, such as an insert placed inside a sleeve, or a portion of a sleeve, between the sleeve or portion, and the reinforcing bar. The clamp used to press the sleeve segment onto the reinforcing bar ends may also have a variety of forms, such as including bolts, tapered collars, or fingered collars.

WO 2005/045151 A2